

# Change Management for life-cycle support from hybrid PNF and VNF management perspective

Yaoguang Wang, Ulas Kozat, Leilei Zhie, Huawei
Xiang Li, CMCC
2018-6-21

#### Outline

Status of Change management (CM) in ONAP

The motivation and proposal

Casablanca functional requirements

#### Status of CM in ONA

#### From CM Team:

- They finished a CM use case in Beijing release, taking vCPE as an example.
- The endorsed functional requirements contains '5G RAN software upgrade':
  - Health check (pre/post)
  - Software download, installation and activation
  - Roll-back for unsuccessful execution
  - •

#### • From 5G Team:

- One objective of 5G deployment (in R3) is 'Target software management'.
- 'Lifecycle management Support' means 'Enhance change management and Close Loop Automation (CLAMP) to support 5G PNF / VNFs'

#### Overlapping!

- <u>5Guc-RAN Deployment (SWCfg\_Mgmt)-Casablanca-Huawei 04282018v3.pptx</u>
- <u>5Guc-RAN Operations (SW upgrade)-Casablanca-Huawei&CMCC 05112018v1.pptx</u>


#### Status of CM in ONAP

- To make a short explanation (need to discussed in both sub-teams), we would like to:
  - In CM use case,
    - define the basic and generic building blocks for both PNF and VNF change management support,
    - design CM work flows as well,
    - extend and discuss CM requirements as stretch R3 goal (shown later).
  - In 5G use case,
    - complete SW management, e.g. 'Expected software version', in PNF PnP
    - Define the **required interfaces** for impacted ONAP projects, e.g. SO, APP-C/SDN-C/VF-C

## Motivation and Proposal


• There are some options for CM, e.g. 'Build-and-replace' and 'in-place

software upgrade'.



## Motivation and Proposal

• There are some options for CM, e.g. 'Build-and-replace' and 'in-place software upgrade'.



'In-place software upgrade' is suitable for PNF.


Besides, which controller is used to handle this upgrade case depends on the VNF/PNF, but the API could be standardized.

Pre/Post-condition test need to be enhanced. They might be complex, however, they could be customized.

\*Note: the full diagram can be found in CM wiki.




## Proposal: Stages for RAN SW upgrade




- Generic procedures and basic building blocks.
- For Pre-Check and Post-Check, they will be mapped to one 'rule'.
- Manual processing mechanism (TBD)
  - candidate: indicator of failure.

## Proposal: Stages for SW upgrade



- Use 'in-place upgrade'
- External controller is used to help Pre/Post-Check
  - HealthCheck only is not enough
  - Pre-Check will fetch and store some necessary state information of PNF in the external controller
  - Post-check will also fetch state info, and the controller do some comparison to make decision.

### Proposal: sequence diagram for swUpgrade



#### Proposal: Beyond SW upgrade

- For VNF, SW upgrade is just one thing.
- VNFD upgrade (TBD).
- VNF Guest OS upgrade (TBD).
- To reuse the previous stages, there are two options to implement VNFD upgrade and VNF Guest OS upgrade:
  - Option 1: add params to the swUpgrade interface
  - Option 2: add two interfaces

- Recommend:
  - CM-related things could and need to be unified for 5G RAN. Because it has to handle both VNF and PNF.

## Casablanca functional requirements

- Support PNF PnP from initial software version to the expected software version
- PNF maintenance can upgrade one software version to the expected software version.
- define the basic and generic building blocks for both PNF and VNF change management support
- design CM work flows
- extend and discuss CM requirements as R3 stretch goals, like VNFD upgrade and VNF Guest OS upgrade.



## Thank You!